

CNet is proud to introduce CFC-22CS media converter providing the simplest way to interconnect any copper 10/100TX port to fiber 100BASE-FX interface. CFC-22CS smoothly transfers data between RJ-45 and 100BASE-FX Single-Mode SC type Fiber ports. CNet media converters are hybrid-networking devices compliant to IEEE 802.3 and 802.3u standards.

**KEY FEATURES**

- TP Port supports Auto-negotiation and Auto-MDI-X
- Operates at Maximum Packet Filtering and Forwarding Rate
- TP Port: 10/100Mbps Full-/Half-duplex
- Fiber Port: 100Mbps Full-/Half-duplex
- Interoperable with 10BASE-TX, and 100BASE-FX Hubs or Switches



**SPECIFICATIONS**

|                      |   |
|----------------------|---|
| Product Name         | 10/100Mbps TP to 100Base-FX Media Converter, SC Type/ Single-Mode/ 20KM   |
| Model Name           | CFC-22CS  |
| Fiber Mode           | Single-Mode   |
| Wave Length          | 1310nm  |
| Fiber Cable          | 9/125µm   |
| Fiber Cable Distance | 20KM  |
| Fiber Connector      | SC Type   |
| TP Ports             | RJ-45 phone-type  |
| LED Indicators       | FX: LINK/ACT<br>FX: FDX/COL<br>TP: LINK.ACT<br>TP: 100  |
| Power Adapter        | External DC5V, 2A   |
| Environment          | Operating Temperature: -20° ~ 70° C (-4° ~ 158° F)<br>Storage Temperature: -40° ~ 80° C (-40° ~ 176° F)<br>Humidity: 10% ~ 90% Non-condensing |
| Certifications       | CE, FCC   |
| Dimensions           | 94 x 70.3 x 26.2 mm (3.7 x 2.77 x 1.03 inches)  |

**ORDERING INFORMATION**

| Model       | Description   |
|-------------|---|
| CFC-22CS(C) | 10/100Mbps TP to 100Base-FX Media Converter, SC Type/ Single-Mode/ 20KM |